



Mitas Generators

| Generator Model | | G5610L/M/LME | | | | | | | 50 Hz | 60 Hz |
|---------------------------|--|----------------|----|----------|--------------------|---|------------------------------|---|-----------------------|--------------------|
| | | Open Version | | | Soundproof Version | | | Voltage (V) | 230 | 110/220 120/240 |
| Dimensions cm (L x W x H) | 70 | 55 | 58 | - | - | - | Continuous Power (kVA) | 5 | 5,3 | |
| | | | | | | | Prime Power (kVA) | - | - | |
| Weight (kg) | 63/67 | | | - | | | Standby Power (kVA) | 5,5 | 6,05 | |
| Fuel Tank (litres) | 4,3 | | | - | | | Power Factor | 1 | 1 | |
| Manual Control Panel | Standard | | | - | | | Continuous Power (kWe) | 5 | 5,4 | |
| Automatic Control Panel | - | | | - | | | Standby Power (kWe) | 5,2 | 5,6 | |
| | | | | | | | Fuel Consumption (75% load) | 260g/kWh 0,88 l/h | 272 g/kWh 0,99 l/h | |
| Engine | 3000 rpm | | | 3600 rpm | | | Alternator | 3000 rpm | 3600 rpm | |
| Model |  LOMBARDINI | | | | | | Model |  nsn generators | | |
| | | 15LD350 | | | | | | SE 100 F | | |
| Continuous Power (kWm) | 4,3 | | | 4,9 | | | Continuous Power (kVA) | 5,0 | 6,5 | |
| Prime Power (kWm) | - | | | - | | | Maximum efficiency@1PF | 75 | 76 | |
| Standby Power (kWm) | 5 | | | 5,5 | | | Exciter | BRUSHLESS | | |
| Aspiration | Natural | | | | | | Wires | 2 | | |
| Cooling System | Air cooled | | | | | | Short-circuit current | 300% | | |
| Speed Governor | Mechanic | | | | | | Poles | 2 | 1 | |
| Number of Cylinders | 1 | | | | | | Phases | | | |
| Displacement | 349 cc | | | | | | Insulation | H | IP21 | |
| Bore x Stroke | 82x66 | | | | | | Voltage Regulation/Condenser | +5%;-10% | | |

The values given in this datasheet are for information purposes only.