


# Mitas Generators

Generator Model	G8000KME						50 Hz	60 Hz	
	Open Version			Soundproof Version			Voltage (V)	230	110/220 120/240
Dimensions cm (L x W x H)	80	56	58	-	-	-	Continuous Power (kVA)	8	9,7
							Prime Power (kVA)	-	-
Weight (kg)	86			-			Standby Power (kVA)	8	9,7
Fuel Tank (litres)	6,9			-			Power Factor	1	1
Manual Control Panel	Standard			-			Prime Power (kWe)	8	9,4
Automatic Control Panel	-			-			Standby Power (kWe)	8	9,4
							Fuel Consumption (75% load)	3,1 l/h	3,7 l/h
Engine	3000 rpm			3600 rpm			Alternator	3000 rpm	3600 rpm
Model	<b>KOHLER</b>						Model	 M 100 LL	
	<b>CS12STG</b>								
Continuous Power (kWm)	9,5			9,7			Continuous Power (kVA)	8	10
Prime Power (kWm)	-			-					
Standby Power (kWm)	9,5			9,7			Maximum efficiency@1PF	80	81
Aspiration	Natural						Exciter	BRUSHLESS	
Cooling System	Air cooled						Wires	2	
Speed Governor	Mechanic						Short-circuit current	300%	
Number of Cylinders	1						Poles	2	1
Displacement	357 cc						Insulation	H	IP23
Bore x Stroke	85x63						Voltage Regulation/Condenser	+5%;-10%	

The values given in this datasheet are for information purposes only