

Model	Continuous Power KVA		Standby Power KVA		Engine Type	Skid Version		Soundproof Version	
	50Hz	60Hz	50Hz	60Hz		Dimensions (L / W / H) cm	Weight (Kg)	Dimensions (L / W / H) cm	Weight (Kg)
G(Q)11P	9	11	10	12	403D-11G	150 x 80 x 110	290	180 x 90 x 125	560
G(Q)16P	13	15.8	14.5	17.5	403D-15G	150 x 80 x 110	350	180 x 90 x 125	620
G(Q)22P	20	24	22.1	26.6	404D-22G	165 x 80 x 120	460	180 x 90 x 125	730
G(Q)35P	30	35	33	38	1103A-33G	180 x 90 x 130	680	220 x 90 x 136	1100
G(Q)50P	45	-	51.3	-	1103A-33TG1	180 x 90 x 130	720	220 x 90 x 136	1150
G(Q)70P	60	68	66	75	1103A-33TG2	180 x 90 x 130	810	220 x 90 x 136	1230
G(Q)90P	80	91	88	100.3	1104A-44TG2	200 x 90 x 130	910	270 x 110 x 175	1570
G(Q)115P	100	114	111.9	126.5	1104C-44TAG2	215 x 100 x 130	1050	270 x 110 x 175	1700
G(Q)150P	135	151	150	165.5	1006TAG	255 x 100 x 140	1230	320 x 110 x 145	1990
G(Q)170P	150	-	165	-	1006TAG2	255 x 100 x 160	1240	320 x 110 x 145	2000
G(Q)200P	180	200	219	219	11006C-E66TAG4	225 x 110 x 170	1480	350 x 130 x 190	2400
G(Q)220P	200	231	229	253	1306C-E87TAG3	275 x 110 x 170	1680	350 x 130 x 190	2600
G(Q)275P	250	-	275	-	1306C-E87TAG6	275 x 110 x 170	1730	350 x 130 x 190	2650
G(Q)300P	275	313	300	344	1606A-E93TAG4	285 x 130 x 170	1760	350 x 130 x 190	2670
G(Q)330P	300	-	330	-	1606A-E93TAG5	285 x 130 x 170	1790	350 x 130 x 190	2700
G(Q)400P	350	400	400	438	2206C-E13TAG2	320 x 130 x 195	2770	440 x 160 x 220	3950
G(Q)451P	400	438	450	500	2206C-E13TAG3	335 x 130 x 195	2910	440 x 160 x 220	4070
G(Q)501P	450	500	500	563	2506A-E15TAG1	345 x 135 x 205	3010	440 x 160 x 220	4150
G(Q)551P	500	500	550	563	2506A-E15TAG2	350 x 135 x 205	3060	440 x 160 x 220	4200
G(Q)600P	600	625	625	687	2806A-E18TAG1A	350 x 175 x 220	3800	490 x 220 x 250	4920
G(Q)700P	650	-	700	687	2806A-E18TAG2	365 x 175 x 220	4060	490 x 220 x 250	5600
G(Q)800P	730	750	800	844	406-23TAG2A	400 x 195 x 230	4800	633 x 230 x 270	6800
G(Q)900P	800	844	900	938	406-23TAG3A	400 x 195 x 230	4800	633 x 230 x 270	6800
G(Q)1100P	1000	-	1093	-	4008TAG2A	490 x 210 x 250	8200	ISO40'	10200
G(Q)1375P	1250	1240	1385	1371	4012-46TWG2A	520 x 230 x 270	8500	ISO40' HC	11000
G(Q)1650P	1500	-	1656	-	4012-46TAG2A	520 x 250 x 310	9600	ISO40' HC	12100
G(Q)2200P	2000	-	2263	-	4016-TAG2A	580 x 300 x 310	12500	ISO40' *	16000

\* INCLUDES EXTERNAL WATER PLANT

Model	Continuous Power KVA		Standby Power KVA		Engine Type	Skid Version		Soundproof Version	
	50Hz	60Hz	50Hz	60Hz		Dimensions (L / W / H) cm	Weight (Kg)	Dimensions (L / W / H) cm	Weight (Kg)
G(Q)25C	-	19.2	-	21.1	X2.5G4	187 x 90 x 120	650	220 x 90 x 136	1200
G(Q)28C	25	-	27.5	-	X2.5G2	187 x 90 x 120	460	220 x 90 x 136	870
G(Q)35C	35	-	38	-	X3.3G1	187 x 90 x 120	580	220 x 90 x 136	1000
G(Q)43C	-	38.4	-	42.2	X3.3G2	187 x 90 x 120	610	220 x 90 x 136	1150
G(Q)44C	40	-	44	-	S3.8G4	187 x 90 x 120	790	220 x 90 x 136	1210
G(Q)55C	50	-	55	-	S3.8G6	1807x 90 x 120	795	220 x 90 x 136	1120
G(Q)66C	60	-	66	-	S3.8G7	210 x 110 x 140	890	270 x 110 x 175	1540
G(Q)110C	100	-	110	-	6BTA5.9G5	237 x 110 x 160	1420	320 x 110 x 170	2170
G(Q)115C	-	114	-	125	QSB5-G5	253 x 110 x 150	1450	320 x 110 x 170	2200
G(Q)138C	125	-	138	-	6BTAA5.9G3	247 x 119 x 160	1470	320 x 110 x 170	2220
G(Q)175C	150	170	175	188	QSB7G3	253 x 110 x 150	1770	320 x 110 x 170	2550
G(Q)176C	160	-	176	-	6BTAA5.9G5	248 x 125 x 160	1770	320 x 110 x 170	2560
G(Q)200C	180	200	200	220	QSB7G4	253 x 110 x 150	1870	320 x 110 x 170	2770
G(Q)220C	200	225	220	250	QSB7G5	267 x 110 x 150	2220	320 x 110 x 170	3100
G(Q)275C	250	284	275	313	QSL9G3	284 x 100 x 150	2290	350 x 130 x 190	3360
G(Q)330C	300	344	330	375	QSL9G5	279 x 100 x 150	2610	350 x 130 x 190	3890
G(Q)385C	350	-	385	-	NAT855G4	302 x 100 x 170	3000	350 x 130 x 190	4300
G(Q)500C	450	513	500	563	QSI5G6/G7	338 x 130 x 180	3900	633 x 230 x 220	4680
G(Q)550C	500	563	550	625	QSI5G8/G9	338 x 130 x 180	4100	633 x 230 x 220	4950
G(Q)700C	636	681	700	750	VTA28G5	396 x 167 x 230	5100	920 x 243 x 270	6320
G(Q)880C	800	909	880	1000	QSK23G3	418 x 188 x 230	5300	820 x 243 x 270	6780
G(Q)1000C	910	1029	1000	1125	QST30G3	423 x 167 x 210	5840	633 x 230 x 270	7810
G(Q)1100C	1000	1138	1100	1250	QST30G4	433 x 222 x 234	6035	633 x 230 x 270	8000
G(Q)1400C	1275	1418	1400	1610	KTA50G3	486 x 222 x 210	9050	633 x 230 x 270	11600
G(Q)1650C	1400	-	1675	-	KTA50G8	573 x 222 x 290	10100	920 x 243 x 299	15600